AX3 LightDrop™

Data sheet

Optical

Colours
RGBW

Total LED power
15W

Luminous Flux
390Lm

Emittance (@2m)
1300Lx

Strobe
0-25Hz

Beam Angle
13 °

Pixels
1

Construction

Housing
ABS

IP Rating
IP65

Relative humidity
0-100%

Operating Temperature
0-40 °C
32-104 °F

Weight
0.679kg
1.4Lbs

Dimensions (with bracket)
120 x 59 x 114 (mm)
7.4 x 2.3 x 4.4 (inches)

Accessories

Charger
AX3-CHR (Included)

Hooks (3)
AX3-EBLT (Included)

Rubber Feet (4)
AX3-FEET (Included)

Bracket
AX3-STA (Included)

30° diffuser
AX3-DDSK30 (Included)

120°diffuser
AX3-DDSK-120(Included)

Wallwash diffuser
AX3-WWDSK

Diffuser dome
AX3-DDM

Charging case
AX3-CHRCSE

Clamp
AX3-CLP

Electrical

Battery
LG Chem Lithium-ion

Battery Lifetime
70% after 300 cycles

Battery Runtime
Up to 20 hours

LED Lifetime
50.000 Hours

Charging time (nominal)
7 Hours

Input Voltage (charger)
90-264V 47-63Hz

Input voltage (light)
5V 2.5A

Control

Wireless Modules
865-870MHz
902-928MHz
2.4GHz

Range
300m | 330 Yards

DMX
Supports CRMX and W-DMX