



AX5 TriplePAR™

Data sheet






Optical

- Colours
RGBAW
- Total LED power
45W
- Luminous Flux
1080Lm*
- Emittance (@2m)
4800Lx*
- CRI
92
- Strobe
0-25Hz
- Beam Angle
13°
- Pixels
1

Construction



- Housing
Aluminium
- IP Rating
IP65
- Relative humidity
0-100%
- Operating Temperature
0-40 °C
32-104 °F
- Weight
3.4kg
- Dimensions
141 x 190 x 214 (mm)

Accessories

-  IR remote control
ARC1
-  32° Flood filter
AX5-FF(included)
-  17°x 46° Wallwash filter
AX5-WWF (Included)
-  Spigot (3/8" & 1/4"-20 threads)
AX1-BLT
-  Charging case
AX5-CHRSE

Electrical

- Battery
LG Chem Lithium-ion
- Battery Lifetime
70% after 300 cycles
- LED Lifetime
50.000 Hours
- Charging time (nominal)
5 Hours
- Input Voltage
90-264V 47-63Hz
- Input Current
1.8A/115VAC ~ 1.0A/230VAC
- Inrush Current
Cold start 30A/115VAC ~ 60A/230VAC



Control

- Wireless Modules
865-870MHz
902-928MHz
2.4GHz
- Range
300m | 330 Yards
- DMX
Supports CRMX, W-DMX and XLR-DMX

